



Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone:(818) 701-4933 Fax: (818) 701-4939

MBRB1030CT **THRU** MBRB1060CT

10 Amp Schottky

Barrier Rectifier 30 to 60 Volts

D²-PAK 2 ח С

DIMENSIONS

INCHES

Α	MIIN	WAX	IVIIN	WAX				
А	.320	.359	8.13	9.14				
В	.380	.411	9.65	10.45				
С	.160	.190	4.06	4.83				
D	.020	.035	0.51	0.89				
Е	.045	.055	1.14	1.40				
G	.095	.105	2.41	2.67				
Н	.096	.120	2.43	3.03				
J	.014	.021	0.35	0.53				
K	.090	.110	2.29	2.79				
S	.575	.625	14.60	15.80				
V	.045	.055	1.14	1.40				
W	0	.006	0	0.15				
SUGGESTED SOLDER PAD LAYOUT								
		18.	79	.065 1.65				

Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
 Epoxy meets UL 94 V-0 flammability rating
 Moisture Sensitivity Level 1

- Meatl of Silicon Rectifier, Majority Conducton Halogen free available upon request by adding suffix "-HF" Guard ring for transient protection
- Low Forward Voltage Drop and Low Power Loss
- High Current Capability, High Efficiency

Maximum Ratings

Operating Temperature: -55°C to +125°C Storage Temperature: -55°C to +150°C

MCC Catalog Number	Maximum Reccurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBRB1030CT	30V	21V	30V
MBRB1035CT	35V	24.5V	35V
MBRB1040CT	40V	28V	40V
MBRB1045CT	45V	31.5V	45V
MBRB1050CT	50V	35V	50V
MBRB1060CT	60V	42V	60V

Electrical Characteristics @ 25°C Unless Otherwise Specified


iooti ioui onaluotoi iotioo 😸 20 0 onioos otiioi mico opoonio					
Average Forward Current	$I_{F(AV)}$	10 A	T _C = 95°C		
Peak Forward Surge Current	I _{FSM}	125A	8.3ms, half sine		
Maximum Instantaneous Forward Voltage	V_{F}	.55V	I _{FM} = 5A; T _J = 25°C		
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	0.5mA	T _J = 25°C		
Typical Junction Capacitance	С	200pF	Measured at 1.0MHz, V _R =4.0V		

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7.

^{*}Pulse Test: Pulse Width 300µsec, Duty Cycle 1%



RATING AND CHARACTERISTIC CURVES MBRB1030CT thru MBRB1060CT






FIG.3 - TYPICAL REVERSE CHARACTERISTICS




FIG.4 - TYPICAL FORWARD CHARACTERISTICS





FIG.5 - TYPICAL JUNCTION CAPACITANCE





Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 800pcs/Reel
Part Number-BP	Tube: 5Kpcs/Ctn

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.