

# Fuse - FUSE 10,3X38 20A PV - 3061363

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Fuse, 10.3x38 mm, up to 1000 V DC, gPV characteristics

### Why buy this product

- 10 x 38 midget fuses for reliable protection of PV modules and their control system
- ☐ Designed in accordance with the photovoltaic standard IEC 60269-6



# **Key Commercial Data**

Packing unit	10 STK
GTIN	4 046356 523790
GTIN	4046356523790

# Technical data

### General

Color	white
Flammability rating according to UL 94	V0
Maximum power dissipation for nominal condition	2.9 W

#### **Dimensions**

Length	38 mm
Diameter	10.3 mm

#### General

Fuse	Midget / 10.3 x 38
Connection in acc. with standard	IEC 60269-6
Nominal current I <sub>N</sub>	20 A
Nominal voltage U <sub>N</sub>	1000 V DC

#### Standards and Regulations



# Fuse - FUSE 10,3X38 20A PV - 3061363

# Technical data

## Standards and Regulations

Connection in acc. with standard	IEC 60269-6
Flammability rating according to UL 94	V0

## **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals	
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC [A[	EAC-Zulassung

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com